





Motor Condition Monitoring Without Sensors

A New Approach in Predictive Maintenance **e-MCM**

The Artesis e-MCM is a powerful online condition monitoring, predictive maintenance and power meter tool intended for critical AC rotating equipment. The patented machine learning algorithm of e-MCM enables comprehensive fault detection up to 6 months in advance. With around the clock monitoring and real-time model-based voltage and current analysis, e-MCM can detect electrical, mechanical as well as process faults of fixed, variable speed motors and generators while providing all the benefits without the high complication and cost of traditional systems.

Artesis e-MCM monitors the condition of equipment driven by an electric motor, effectively using the motor itself as a sophisticated transducer. It requires only connection into the motor's electrical supply, avoiding the need or specialised sensors. Because Artesis e-MCM is permanently installed, it provides continuous fault monitoring and does not depend on expensive manual data collection.





$\xrightarrow{\circ}^{\diamond} \mathsf{Fault} \mathsf{Coverage}$

- Loose foundation/ components
- Mechanical unbalance/missalignment
- Transmission faults
- Driven equipment faults
- . Gearbox, belt, coupling
- Bearing
- Stator and rotor faults
- Internal electrical faults
- . External electrical faults

က္သြို Process Faults

- High energy consumption
- Low efficiency
- Cavitation in pumps
- Flow turbulence in fans, blowers
- Filter and heat exchanger fouling
- Lubrication
- Oversize/undersize motors
- Air flow disturbance



- Vr, Vs and Vt
- Ir, Is and It
- Frequency
- Voltage Unbalance
- Current Unbalance
- Motor Load
- Power Factor
- Active Power
- Reactive Power
- Total and odd harmonics

It Simply Works

e-MCM provides clear information for fault detection, diagnostics, time to failure and corrective actions. It only demands your attention when it detects a problem. This makes it very attractive in comparison with walkaround systems which require considerable effort and cost just to find out whether you have a problem or not. It automatically assesses the severity of any variations from normal operation and presents the results of its sophisticated analysis to the user in a simple, compelling traffic light display. As a fault starts to progress, the traffic light changes from green to orange, indicating that maintenance action will be required in the future. A red traffic light indicates that the high severity of the problem requires immediate attention.



Name	12/8/2018	12(9)(2018	12(35/0018	22/12/2018	12/22/2018	12(22)(2013)	12(14(0108	12 15 0008	12/06/2018	12(17/2018	12/18/0018	12(19)2118	12/20/2018	12/03/0918	12(02/3118	12/11/05 08	12/34(2118	12(25)(20.18	12/06/0018	12(27)2018
- dje boshost																				
- A races																				
- 🙏 400M																				
- R HEROZH, FEROIST																				
HP 1250 KWHRUK, KOMPRESOR.																				
9 6304																				
REAL MARKED SOUTH A STREET																				
- 式 stes																				
POSD/POMPA																				1
3 PH_221																				
a nan																				
A 1245																				
A Man												-								
A 101																				
R071																				
- <u>8</u> a			_	_	_			_		_		_		_			_	_		
COLD GROKOWPRESON												1								
PESS POHEN	_		-			-		_				_					-		-	
KILLGARD KEMPRESOR					1															
BADLE KORNEDAL KOMPEDIA																				
- <u>R</u> sc			_	_	_			_		_		_	_	_	_		_		_	
🗿 Pil-KEA						1						1			1				1	
2 PL-08																				
R162																				
1000																				
9 79421																				
A 10.404																				
S PELLA					-	-	-	_	-		-	_	_	_	_	-	_	-		
¥2210																				
3 C10A																				
C1038																				
- 2,45																				
a nas		1	1	1	1	1	1	1	1				1		1				1	
120	1	-										100								

Artesis Enterprise Software

Artesis				Welcome, admin 1 🕷 Beck to e	deșis 14 Legra
alegery	anagory	 Select Equipment 	7.8200 (14/81.1	Mannanana Infe	
taous Information				Active prover(bW)	· Constant of the
Watch	Load Pete	Type Descrip	otion Occurrence	- month	
Mode : Monitor				al	-
	THD		Frequency.		-m -
		3.15%	50.02Hz	alan, jaqua, jaqua, jaqar, jaqar, jaqar, jaqar alan, jaqar, jaqar, jaqar, jaqar, jaqar, jaqar	
ower factor	TH0	3.15%	Frequency 50,02Hz	Image: Second	
		3.15%	50.02Hz	Physical processions: Hereiner 2010 Theorem	Constant ages
10000 factor	No Current	3.15% 3	5 50.02Hz 500	а с с с с с с с с с с с с с с с с с с с	Contrast ops Rentered ago o n mp Ap

Equipment status info	Diagramis list	Status summary		INCOME STOP	DATA dK/Lea	ming 🐥 Watch 🔺 F	NIT ALAD
Today	Vesterday	Name	Status	Power factor	Total run hour	Total watt hour	Active pow
DK		TA3000 CIXISI-1		84.98%	0 day 6 hours	2,839.64kWh	472.74kW
Width Load Gamm Errar		ATLAS COPCO CIKISI ZH 7000 4	11	99.88%	0 day 5 hours	3,521.57kWh	(85.83kW
		TA3000 CIKISI 2		84.05%	D day 6 hours	2/422.03kWh	354.97%W
		TA3000 CIKISI-4		84.37%	0 day 4 hours	1,737.51kWh	371.97kW
Name Equipment 0 Watch Equipment 2	Alarm Equipment: 0 Watch Equipment: 0	TA3000 CIXISE3	н	57,06%	0 day 4 hours	517.31kWh	107.43kW
Watch Injurprised: 2 Total Populprised: 8	Tenal Population: 5	TA3000 CIKISI 5, Atlas Copce 630-9		50.37%	0 day 5 hours	2,857.01kWh	393,91kW
900- m				Te	ial watt hour per hour		
_1	2000 7	HOURY ON	a Month				
200	101-	2500					
And A Contract of	100-	2000					
	1204-	1500					
400-	100-	1300					
200-	80- 80-	500					
	60-		A COMP	and and a	and party	and the second	
	-		9 9	8 8	Same and and	a for the second	and and all

Artesis IoT Software

Permanently installed Software provides processed data results in an actionable form which greatly reduces the specialist diagnostic skills required of the user, making the benefits of condition monitoring available to many groups who have considered it too difficult in the past.

Artesis Condition Monitoring System e-MCM

The patented NASA-developed technology provides machine learning capability in a compact, affordable, panel-mounted instrument. e-MCM can detect wide variety of faults by automatically teaching itself about the normal operation environment of your equipment so that it can accurately identify and diagnose faults long before they become a threat.



e-MCM system offers various remote monitoring options ranging from local to cloud based IoT monitoring.

- AES Software (Windows based) running on local server
- Artesis Web IoT Platform on cloud server
- 3rd party monitoring software integration via OPC



The Artesis e-MCM software allows users detailed analysis with Power Spectral Density and Trend Analysis tools for root causes of the faults. e-MCM is specifically designed to be self-sufficient, only requiring your intervention when it detects a problem. It can also act as an intelligent component of a

complete, plant-wide monitoring and diagnosis system. You can connect it into your own systems using its standard interfaces, allowing results to be presented to your staff through existing display systems. Artesis can supply MCMScada software to collect and manage information from all your Artesis MCM units, provide enhanced diagnostic capability, and to allow remote operation of the complete system. This can also allow Artesis to help out with your condition monitoring program by providing remote advanced interpretation services.



PSD Analysis Screen

رچ Key Benefits

- Decrease on maintenance cost
- Productivity increase
- Equipment life extension
- Energy saving
- Improved process safety



Watch e-MCM video



- Oil & Gas
- Energy
- Cement
- Metal
- Pharmaceutical
- Automotive
- Water
- Transportation
- Food & Beverages
- Buildings





Trend Screen



- Compressors
- Fans
- Pumps
- Conveyors
- Generators
- Motor Driven Equipment
- AHU
- Mixer



Turbine Controls Ltd

52 Kenilworth Drive, Oadby, Leicester, LE2 5LG United Kingdom

+44 (0)116 271 7248 🕔

sales@tcluk.net support@tcluk.net

tcluk.net 🌐

